

CASIO® TE-2200

Simple, yet powerful scanning
cash register to help you
manage your business
transactions



www.casio.co.uk/systems

CASIO®

The CASIO TE-2200 features a raised keyboard, high speed dual printers, barcode scanning and a bright customer display making it ideal for fast sale processing in a retail environment.

CASIO® TE-2200

Receipt and journal printer



The TE-2200 features two fast, 58mm wide thermal printers. Printing speeds of 14 lines per second mean your customers will receive their receipts quickly. And to give your business a professional appearance, graphic logos and watermarks can also be printed. With easy drop-in

paper loading for simple paper roll replacement, the TE-2200 ensures fast and efficient operation.

Barcode scanning

The TE-2200 can be used in conjunction with a barcode scanner to improve the efficiency of your business. This function allows up to 5000 products to be scanned into the cash register, ensuring that products are sold at the correct price and eliminating the need to manually enter prices. Scanning a products' barcode at the point of sale, allows you to use shelf edge labels to indicate product pricing, eliminating the need for staff to individually price each item.

Display

The TE-2200 features a bright, contrast adjustable 5.2-inch LCD operator display with 2 x 16 character lines to display product details and a 7 digit display for product price. This means your staff can easily see the details of the items they are selling to ensure accuracy. A standard pop-up rear display ensures your customers can see the price they are paying, giving them peace of mind.



Help function

The TE-2200 is simple to operate, however there is also a user friendly "HELP" button on the keyboard. Answers to frequently asked questions such as how to programme the time and date can be printed on the receipt printer for easy reference.



Peripherals

For maximum flexibility, the TE-2200 features two serial ports for direct connection to PC, modem for connecting to head office, external remote printer, slip printer for printing guest receipts or validation and scanner for barcode reading.

Reports and useful functions

Daily reports can be printed on the TE-2200 using compressed printing. Other useful functions include clerk interrupt, scheduler function, set menu function, arrangement function and memory allocation.

- Financial
- Transaction
- Department
- PLU
- PLU stock
- Table analysis
- Open check
- Monthly
- Hourly
- Flash
- Group
- Clerk
- Time & attendance
- Scanning PLU
- Scanning PLU stock
- Inactive PLU

Z	10-10-2012	21:10	Mode symbol/date/time
C01	MC#01	000045	Clerk descriptor/Mc-No./consecutive No.
Z	SCAN	PLU	0001
			Report header/title/reset counter (Z only)
			2001026
			Report code
DEPT01			Classified title (by group/dept)
SCAN_PLU001		382	Scanning PLU character/quantity
	17.07%		Sales ratio/total
	#4901234567894		Scanning PLU code
		-1,583.47	
SCAN_PLU002		382	
	38.01%		
		-3,526.46	
	#4989012345674		
		382	
	10.49%		
		-973.45	
	#4967890123454		
		1253	Total of this classification
		-9,275.83	
DEPT02			
SCAN_PLU010		453	
		-1,583.47	
	#4945678901234		
		243	
		-10,375.93	
TL		12653	Quantity total
		-273,375.93	Amount total

Data storage

The TE-2200 features a Compact Flash (CF) card slot, which allows reports to be saved to a CF card for easy transferral to PC for manipulation with other software. Program data can also be stored for backup purposes.

Options

Model No.	Product
SP-1300	Slip Printer
UP-360	External Printer (thermal)

Specifications

Displays	Operator	5.2-inch backlit LCD
	Customer	2 x 16 characters / 10 digits, 7 segments
Printer	Printing method	Two-station thermal printer
	Printing speed	14 lines/sec. (max.)
	Paper width	58mm +0/-1mm x 80
	Paper loading	Drop-in paper loading
Memory back-up		90-day data backup (vanadium lithium battery)
Power consumption		AC 230V- Operating 0.25A, Standby 0.05A
Operating environment		Temperature - 0 to 40°C
		Humidity -10 to 90%RH
Dimensions (w/ med. drawer)		227 (H) x 400 (W) x 450 (D) mm
Weight (w/ med. drawer)		Approx. 12 kg

Specifications and design are subject to change without notice